

# 2026 OUTLANDER ELECTRIC



White

## PACKAGE HIGHLIGHTS

- Liquid-cooled system : Battery, inverter, motor and on-board charger
- Charging from 20% to 80% in as low as 50 min
- Up to 47 miles (75 km) of range
- High and Low gear allowing full work capacity
- Engine modes and speed limiter
- Dedicated tires for optimal noise and vibrations level
- 3-level regen braking
- On-the-fly reverse capabilities
- 5 in. colored display
- Front and rear bumpers
- LED headlights and tail lights, specific LED POD light

| ENGINE              | Electric                                                  |
|---------------------|-----------------------------------------------------------|
| Type                | 47 hp / 53 lb-ft, ROTAX® E-POWER, Liquid-cooled           |
| Power               | Peak: 47 hp (35 kW)<br>Continuous: 27 hp (20 kW)          |
| Torque motor        | Peak: 53 lb-ft (72 Nm)<br>Continuous: 21 lb-ft (28Nm)     |
| Top Speed/Sustained | High gear: 50 mph (80 km/h)<br>Low gear: 28 mph (45 km/h) |

| BATTERY                              |                                                                                                                |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Battery type                         | Integrated, Lithium-ion                                                                                        |
| Battery operating temperature range  | From -20°C to 40°C<br>(-4 Fahrenheit to 104 Fahrenheit)                                                        |
| Battery capacity                     | 8.9 kWh                                                                                                        |
| Cooling system                       | Liquid-cooled : Battery, inverter and on-board charger<br>Integrated AC heater for charging at low temperature |
| Estimated range (when fully charged) | Tested in accordance with WMTC*: 50 miles (80 km)<br>Average utility range*: 31 miles (50 km)                  |
| Fonction                             | Regen braking with 3 levels adjustments                                                                        |
| Charger                              | On-board charger 6.6 kW Level 2<br>(compatible with level 1 charging)                                          |
| Connector type                       | Type 2 IEC 62196 with integrated LED light                                                                     |
| Charging time Level 2 (240 V)        | 50 min (20 - 80 %)<br>1 hour 30 min (0 - 100%)                                                                 |
| Charging time Level 1 (120 V)        | 3 hours 10 min (20 - 80%)<br>5 hours 15 min (0 - 100%)                                                         |

| DRIVE TRAIN        |                                                                         |
|--------------------|-------------------------------------------------------------------------|
| Transmission       | L / N / H / P<br>Reverse activated via start button                     |
| Drive Train        | Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential |
| Driving assistance | Work / Standard / Sport modes<br>Speed limiter                          |
| Power Steering     | Tri-Mode Dynamic Power Steering (DPS)                                   |

| SUSPENSIONS      |                                           |
|------------------|-------------------------------------------|
| Front Suspension | Double A-arm<br>9.75 in. (24.8 cm) travel |
| Front Shocks     | Twin tube                                 |
| Rear Suspension  | Double A-arm<br>10.25 in. (26 cm) travel  |
| Rear Shocks      | Twin tube                                 |

| TIRES / WHEELS     |                                    |
|--------------------|------------------------------------|
| Front & Rear Tires | XPS Recon Force 26 x 8/10 x 14 in. |
| Wheels             | 14 in. cast aluminum               |

| BRAKES |                                                             |
|--------|-------------------------------------------------------------|
| Front  | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| Rear   | Single 214 mm disc brake with hydraulic twin-piston caliper |

| DIMENSIONS / CAPACITIES |                                                 |
|-------------------------|-------------------------------------------------|
| Estimated Dry Weight    | 875 lbs (398 kg)                                |
| L x W x H               | 86.7 x 47.6 x 48 in. (220.2 x 120.9 x 122 cm)   |
| Wheelbase               | 53 in. (134.5 cm)                               |
| Ground Clearance        | 12 in. (30.5 cm)                                |
| Seat Height             | 38 in. (96.7 cm)                                |
| Rack Capacity           | Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg) |
| Storage Capacity        | 9 gal (34 L)                                    |
| Towing Capacity         | 1,830 lb (830 kg)                               |

| FEATURES          |                                                                  |
|-------------------|------------------------------------------------------------------|
| Gauge             | 5 in. colored display                                            |
| DC - DC converter | Continuous 500W (at all speed including at idle)                 |
| Instrumentation   | Phone charger with 1xUSB-A and 1xUSB-C outputs                   |
| Ignition          | RF Digitally Encoded Security System (D.E.S.S.™)                 |
| Lighting          | LED headlights and tail lights<br>LED signature<br>LED POD light |
| Winch             | N/A                                                              |
| Seat              | Removable passenger seat                                         |
| Handlebar         | Standard                                                         |
| Protection        | Front and rear bumpers<br>Full skid plate                        |
| Hitch Type        | 2 in. hitch receiver                                             |

| WARRANTY & EXTENDED SERVICE |                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------|
| Factory warranty            | Battery: 5 years (12,427 miles / 20,000 km limit)<br>Vehicle: 2-years BRP Limited warranty |



REQUEST A QUOTE



©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.